

Drip edge no. 5



The drip edge is used for the production of professional Closures used on the roof.

The use of the profile ensures controlled water drainage on the roof surfaces and protects the covering from penetrating water. The universally applicable drip edge is suitable for many roof coverings and gives the roof a visual Rounding.



Coverage: Bitumen shingles, slate, roof tiles, slate welding membranes

Material: Aluminium natural, aluminium coloured, copper and zinc

Fastening: Spenglers screws and cardboard nails

Cut: 168 mm or special cut according to Sketch
(width before mechanical processing)

Article number - Cut 168 mm

	Alu-nature	Alu-anthracite *	Alu-brown *	Alu-white *
1 m	42 600 36 89 3274	42 600 36 89 3168	42 600 36 89 6060	40 55 66 400 6499
2 m	42 600 36 89 3267	42 600 36 89 3793	40 55 66 400 6475	40 55 66 400 6550
	Alu-green *	Alu-brick red *	Alu-sepia brown *	Zinc
1 m	40 55 66 400 6512	40 55 66 400 6505	40 55 66 400 6529	40 55 66 400 6536
2 m	40 55 66 400 6574	40 55 66 400 6567	40 55 66 400 6581	40 55 66 400 6598

Sketch

Connection

	Cut in mm	a in mm	b in mm	c in mm	
	168	83	25	60	

