

Drip edge no. 4



The drip edge is used for the production of professional roof and connections on the roof. The use of the profile ensures controlled water drainage on the roof surfaces and protects the covering from penetrating water. The universally applicable drip edge is suitable for many roof coverings and gives the roof a visual Rounding.




Coverage: Bitumen shingles, roof tiles, slate, welding web
Material: Aluminium natural, aluminium coloured, copper and zinc
Fastening: Spenglers screws and Cardboard nails
Cut: 250 mm or special cut according to Sketch (width before mechanical processing)

Article number - Cut 250 mm

	Alu-nature	Alu-anthracite *	Alu-brown *	Alu-white *
1 m	42 600 36 89 2178	42 600 36 89 2192	40 55 66 400 6253	42 600 36 89 2253
2 m	42 600 36 89 2185	42 600 36 89 2208	40 55 66 400 6260	42 600 36 89 2260
	Alu-green *	Alu-brick red *	Alu-sepia brown *	Zinc
1 m	40 55 66 400 6291	40 55 66 400 6277	40 55 66 400 6314	42 600 36 89 2277
2 m	40 55 66 400 6307	40 55 66 400 6284	40 55 66 400 6321	42 600 36 89 2284

Sketch



Connection

Cut in mm	a in mm	b in mm	β in °	
250	205	30	95	