

Valley flashing



The use of the profile ensures controlled water drainage on the roof surfaces and protects the covering from penetrating water. The universally applicable valley flashing is suitable for many roof coverings and gives the roof a visual Rounding.





Coverage: Bitumen shingle, slate, roof tiles
Material: Aluminium natural, aluminium coloured, copper and zinc
Fastening: Aluminium hook, spenglers screws and Cardboard nails
Cut: 333 mm and 400 mm (on request)
or special cut according to Sketch
(width before mechanical processing)

Article number - Cut 333 mm

1 m	Alu-nature 42 600 36 89 0105	Alu-anthracite * 40 55 66 400 5829	Alu-brown * 40 55 66 400 5805	Alu-white * 40 55 66 400 5843
2 m	42 600 36 89 0228	40 55 66 400 5836	40 55 66 400 5812	40 55 66 400 5850
1 m	Alu-green * 40 55 66 400 5881	Alu-brick red * 40 55 66 400 5867	Alu-sepia brown * 40 55 66 400 5904	Zinc 40 55 66 400 5928
2 m	40 55 66 400 5898	40 55 66 400 5874	40 55 66 400 5911	40 55 66 400 5935

Sketch

Connection

	Cut in mm	a in mm	b in mm	β in °	
	333 400	149 180	149 180	130 130	

* Colored sheet metal is only coated on one side! · Note for valley flashing: Color side inside

If the color side differs, please specify changes!