

## Wall flashing no. 2



The wall flashing no. 2. is used for the production of professional roof and connections on the roof and wall. It is the connecting plate between the roof surface and the vertical component. The use of the profile ensures controlled water drainage on the roof surfaces and protects the covering from penetrating water. The universally applicable wall flashing is suitable for many roof coverings and gives the roof and wall a visual Rounding.




Coverage: Bitumen shingle, roof tiles and slate  
Material: Aluminium natural, aluminium coloured, copper and zinc  
Fastening: Aluminium hook, spenglers screws and Cardboard nails  
Cut: 200 mm (on request) and 250 mm  
or special cut according to Sketch  
(width before mechanical processing)

### Article number - Cut 250 mm

<b>1 m</b>	<b>Alu-nature</b> 42 600 36 89 0044	<b>Alu-anthracite *</b> 42 600 36 89 4431	<b>Alu-brown *</b> 40 55 66 400 6024	<b>Alu-white *</b> 42 600 36 89 4493
<b>2 m</b>	42 600 36 89 0167	42 600 36 89 4448	40 55 66 400 6031	42 600 36 89 4509
<b>1 m</b>	<b>Alu-green *</b> 40 55 66 400 6048	<b>Alu-brick red *</b> 42 600 36 89 4479	<b>Alu-sepia brown *</b> 42 600 36 89 4455	<b>Zinc</b> 42 600 36 89 4516
<b>2 m</b>	40 55 66 400 6055	42 600 36 89 4486	42 600 36 89 4462	42 600 36 89 4523

### Sketch



### Connection

Cut in mm	a in mm	b in mm	β in °
200	100	80	95
250	155	80	95



\* Colored sheet metal is only coated on one side! · Note for Wall flashing no. 2: Color side inside  
\*If the color side differs, please specify changes!\*