

Wall flashing no. 3



The wall flashing is used to create professional flashings on the roof. It is the connecting plate between the roof surface and the vertical component.

The use of the profile ensures controlled water drainage on the roof surfaces and protects the covering from penetrating water. The universally applicable wall flashing is suitable for many roof coverings and gives the roof a visual Rounding.




Coverage: Bitumen shingle, slate, roof tiles, welding web
Material: Aluminium natural, aluminium coloured, copper and zinc
Fastening: Spenglers screws and Cardboard nails
Cut: 167 mm or special cut according to Sketch
(width before mechanical processing)

Article number - Cut 167 mm

	Alu-nature	Alu-anthracite *	Alu-brown *	Alu-white *
1 m	40 55 66 400 6086	40 55 66 400 6109	40 55 66 400 6093	40 55 66 400 6116
2 m	42 600 36 89 4073	40 55 66 400 6185	40 55 66 400 6178	40 55 66 400 6192
	Alu-green *	Alu-brick red *	Alu-sepia brown *	Zinc
1 m	40 55 66 400 6130	40 55 66 400 6123	40 55 66 400 6147	40 55 66 400 6154
2 m	40 55 66 400 6215	40 55 66 400 6208	40 55 66 400 6222	40 55 66 400 6239

Sketch

Connection



Cut in mm	a in mm	b in mm	β in °
167	73,5	10	100



* Colored sheet metal is only coated on one side! · Note for Wall flashing no. 3: Color side inside

If the color side differs, please specify changes!