

Counter flashing + Extruded counter flashing



The counter flashing is used for the production of professional roof and connections on the roof and facade. It is the end rail between the roof surface and the vertical component. In addition, it prevents the ingress of Rainwater between the components. The universally applicable counter flashing is suitable for many roof coverings and gives the roof a visual Rounding.



Coverage: Welding web, bitumen shingle, roof tiles, slate
Material: Aluminium natural, aluminium coloured, copper and zinc
Fastening: Spenglers screws
Cut: 70 mm or special cut according to Sketch
(width before mechanical processing)

Article number

1 m	Alu-nature 42 600 36 89 0013	Alu-anthracite * 42 600 36 89 5407	Alu-brown * 40 55 66 400 6611	Alu-white * 40 55 66 400 6628
2 m	42 600 36 89 0136	42 600 36 89 5360	40 55 66 400 6673	40 55 66 400 6680
1 m	Alu-green * 40 55 66 400 6635	Alu-brick red * 42 600 36 89 5353	Alu-sepia brown * 40 55 66 400 6642	Zinc 40 55 66 400 6659
2 m	40 55 66 400 6697	42 600 36 89 5391	40 55 66 400 6703	40 55 66 400 6710

Article number - extruded counter flashing

1 m	Alu-nature 4260036898156	2 m	Alu-nature 4260036898163	
------------	------------------------------------	------------	------------------------------------	--

Sketch

Connection

	Cut in mm	a in mm	
	70	57	

Sketch - extruded counter flashing

Connection

	Cut in mm	a in mm	
	70	60	

* Colored sheet metal is only coated on one side!