

SDF roof and facade system



The fastening is done with roof and facade construction screws (Minimum dimensions 6.0 x 38 mm, sealing disc E22). Per plate at least 5 screws are required. In the overlap area of the plates a sealing tape must be glued.

Tip:

An uncovered area of up to 5 cm per front side can be covered by SDF box gutter.




Material: Aluminium natural, Aluminium coloured, Zinc, Copper
Fastening: SDF roof and facade system
Profile length: 1180 mm or 2000 mm
Profile width: 585 mm
profile height: 20 mm



Article number

1180 mm 2000 mm	Alu-nature 40 55 66 400 1654 40 55 66 401 2414	Alu-anthracite * 40 55 66 400 1715 40 55 66 401 2407	Alu-brown * 40 55 66 400 6758	Alu-white * 40 55 66 400 6765
1180 mm 2000 mm	Alu-green * 40 55 66 400 6772	Alu-brick red * 40 55 66 400 1920 40 55 66 401 2391	Alu-sepia brown * 40 55 66 400 6789	Zinc 40 55 66 400 6796

Sketch

	Cut in mm	a in mm	b in mm	c in mm	d in mm
	663	24	25	155	30

Connection

 <p>Overlap area at least 100 mm</p> <p>1180 / 2000 mm</p> <p>585 mm</p> <p>Overlapping area at least 1 triangular point</p>	 <p>sealing tape</p>
---	--

* Colored sheet metal is only coated on one side!