

Ridge flashing



The ridge flashing is used for the production of professional trimmings and Connections on the roof used. The use of the profile ensures for controlled water drainage on roof surfaces and protects the cover from penetrating water. The universally ridge flashing sheet is suitable for many roof coverings and gives the roof a visual rounding.



Coverage: Bitumen shingle, slate and welded sheeting
Material: Aluminium natural, aluminium coloured, copper and zinc
Fastening: Spenglers screws and cardboard nails
Cut: 168 (on request), 200 and 250 mm or special cut according to sketch
(width before mechanical processing)

Article number - Cut 200 mm


1 m	Alu-nature 42 600 36 89 1775	Alu-anthracite * 42 600 36 89 1799	Alu-brown * 42 600 36 89 1812	Alu-white * 42 600 36 89 1850
2 m	42 600 36 89 1782	42 600 36 89 1805	42 600 36 89 1829	42 600 36 89 1867
1 m	Alu-green * 40 55 66 400 5522	Alu-brick red * 42 600 36 89 1836	Alu-sepiabrown * 40 55 66 400 5546	Zinc 42 600 36 89 1874
2 m	40 55 66 400 5539	42 600 36 89 1843	40 55 66 400 5553	42 600 36 89 1881

Article number - Cut 250 mm

1 m	Alu-nature 42 600 36 89 0068	Alu-anthracite * 42 600 36 89 1911	Alu-brown * 40 55 66 400 5584	Alu-white * 42 600 36 89 1973
2 m	42 600 36 89 0181	42 600 36 89 1928	40 55 66 400 5591	42 600 36 89 1980
1 m	Alu-green * 40 55 66 400 5607	Alu-brick red * 42 600 36 89 1959	Alu-sepiabrown * 42 600 36 89 1935	Zinc 42 600 36 89 1997
2 m	40 55 66 400 5614	42 600 36 89 1966	42 600 36 89 1942	42 600 36 89 2000

Sketch

Connection



Cut in mm	a in mm	b in mm	β in °
168	84	84	80
200	100	100	80
250	125	125	80

