

Downspout bracket



with angle pin

with screw

The downpipe is professionally fastened to the wall with the downspout bracket. One bracket clamp is required for each running meter of downpipe. There are 2 types of clamps, depending on the customer's requirements, for knocking in (with an angle pin) or for screwing (with a collar screw) into the wall.


Article number - with angle pin

	galvanized steel			Length in mm
DN 60	42 600 36 89 0716			210
DN 76	42 600 36 89 8019			220
DN 80	42 600 36 89 0518			235
DN 87	42 600 36 89 8026			235
DN 100	42 600 36 89 8033			305

Article number - with screw

	galvanized steel	Steel-anthracite	Steel-brown	
DN 60	42 600 36 89 0709	40 55 66 400 0725	40 55 66 400 2262	
DN 76	42 600 36 89 8095			
DN 80	42 600 36 89 0532	40 55 66 400 0220	40 55 66 400 0091	
DN 87	42 600 36 89 8101			
DN 100	42 600 36 89 8118	40 55 66 400 2736	40 55 66 400 2460	
	Steel-green	Steel-brick red	Steel-white	Length in mm
DN 60	40 55 66 400 3702	40 55 66 400 4358	40 55 66 400 3054	170
DN 76			40 55 66 401 3701	185
DN 80	40 55 66 400 3900	40 55 66 400 4556	40 55 66 400 3252	180
DN 87				190
DN 100	40 55 66 400 4037	40 55 66 400 4686	40 55 66 400 3382	200

Downspout Y-pipe



The downspout Y-pipe provides a connection of side strands from the roof to the downspout.

a / b in mm
300 / 140
295 / 145
297 / 135
320 / 153

Article number

	Alu-nature	Alu-anthracite	Alu-brown	Zinc
DN 60 auf 60	42 600 36 89 1188	40 55 66 401 8607		42 600 36 89 1287
DN 80 auf 80	42 600 36 89 1164	40 55 66 465 2672		42 600 36 89 1263
DN 87 auf 87	42 600 36 89 1133			42 600 36 89 1232
DN 100 auf 100	42 600 36 89 1096			40 55 66 400 8486