

## Eaves tray no. 2



The eaves tray is used to make professional flashings and connections on the roof. It is the transition plate from the roof surface (eaves) to the gutter. The use of the profile ensures controlled water drainage on the roof surfaces and protects the covering from penetrating water. The universally applicable verge termination is suitable for many roof coverings and gives the roof a visual Rounding.




Coverage: Bitumen shingles, roof tiles, slate, welding web  
Material: Aluminium natural, aluminium coloured, copper and zinc  
Fastening: Spenglers screws and cardboard nails  
Cut: 200 (on request) and 250 mm or special cut according to sketch (width before mechanical processing)

### Article number - Cut 250 mm

	Alu-nature	Alu-anthracite *	Alu-brown *	Alu-white *
1 m	42 600 36 89 0082	42 600 36 89 4172	40 55 66 400 5744	42 600 36 89 4233
2 m	42 600 36 89 0204	42 600 36 89 4189	40 55 66 400 5751	42 600 36 89 4240
	Alu-green *	Alu-brick red *	Alu-sepia brown *	Zinc
1 m	40 55 66 400 5768	42 600 36 89 4219	42 600 36 89 4196	42 600 36 89 4257
2 m	40 55 66 400 5775	42 600 36 89 4226	42 600 36 89 4202	42 600 36 89 4264

### Sketch



Cut  
in mm

200  
250

a  
in mm

185  
235



### Connection