

Downspout bracket




The downspout bracket is professionally fastened to the wall with the downpipe clamp. One pipe clamp is required for each running meter of downpipe.
Attachment with collar screw

Length in mm
185

Article number

DN 76	Steel - anthracite 40 55 66 401 3671	Steel - grwy 40 55 66 401 3688	Steel - brown 40 55 66 401 3695	Steel - white 40 55 66 401 3701
-------	---	-----------------------------------	------------------------------------	------------------------------------

Downspout Y-pipe



The downspout Y-pipe provides a connection of side pipes from the roof to the downspout.


Angle: 87,5°

a / b in mm
295 / 145

Article number

DN 76 / DN 76	PVC - anthracite 40 55 66 401 3718	PVC - grey 40 55 66 401 3725	PVC - brown 40 55 66 401 3732	PVC - white 40 55 66 401 3749
---------------	---------------------------------------	---------------------------------	----------------------------------	----------------------------------

Downspout cleanout



The downspout cleanout for installation in the downspout is used to collect rainwater. The sieve serves as a leaf catcher for the downspout and should be removed in winter to avoid the risk of icing. There are special outlet extensions for the downspout cleanout, which are to be attached using a plug connection.

a / b in mm
400 / 200

Article number

DN 76	PVC - anthracite 40 55 66 401 3756	PVC - grey 40 55 66 401 3763	PVC - brown 40 55 66 401 3770	PVC - white 40 55 66 401 3787
-------	---------------------------------------	---------------------------------	----------------------------------	----------------------------------