



| Grate | | | | | | | |
|-------------------|--|--|-----------------|---|---|--|--|
| | | The SAREI grating ensures safe access to the roof. Its special tread surface prevents it from slipping. The gratings are connected with special connecting components; fastening with grating supports. Width: 250mm | | | | | |
| Article number | | | | | | | |
| 1 m 2 m 3 m | galvanized steel 42 600 36 89 0846 42 600 36 89 0853 42 600 36 89 0860 | | 0,6 m 0,88 m | 4 | galvanized steel 42 600 36 89 5377 42 600 36 89 5384 | | |
| | | | | | | | |
| Grating support | | | | | | | |

| for slate | for brick | The grating support is required to attach the grating. The gratings are attached to the grating supports with special anchor nails. The recommended distance between the platform supports is 90 cm. | | | | | | |
|----------------|---------------------------------------|--|-----------|---------------------------------------|---------------------|--|--|--|
| Article number | | | | | | | | |
| for slate | galvanized steel 42 600 36 89 0877 | | for brick | galvanized steel 42 600 36 89 9566 | length in mm 500 | | | |

| Grating connector + mounting screws | | | | | | | | |
|-------------------------------------|--|---|--------|---|--|--|--|--|
| | | The grating connectors serve as connecting pieces for gratings. A set includes 2 galvanized connectors and 1 stainless steel spring. | | | | | | |
| Article number | | | | | | | | |
| Connects | galvanized steel 42 600 36 89 9559 | | Screws | stainless steel 42 600 36 89 9573 | | | | |